



Manual Bucket Pumps Multi-Pressure

Heavy duty pump with 3 position lever to develop 2500 to 5000 PSI (172 to 345 Bar) to adapt pump for different lubricant types and conditions.

Features and Benefits:

- **Tank Capacity:** 35lbs. (16 kg) or 5 gallons (19 liter)
- **Delivery:** Grease: .33oz (9.4 grams) per stroke
Oil: 1 oz. (30 ml) per stroke
- **Lever:** Three position lever develops 2500 to 5000 PSI (172 to 345 Bar)
- **Pump Weight:** 18 lbs. (8 kg)



7149-A4
Shown

Product #	Description	Total Weight	Included Items
7149-4	Multi-Pressure Bucket Pump	18 lbs. (25kg)	N/A
7149-A5	Multi-Pressure Bucket Pump Assembly	21 lbs. (25kg)	Hose Assembly (322434)
7149-E4	Multi-Pressure Bucket Pump Assembly	21 lbs. (25kg)	Hose & coupler assembly (6616-G), Buttonhead fitting (A1188), Plug Button (171134)
7149-F4	Multi-Pressure Bucket Pump Assembly	21 lbs. (25kg)	Hose & coupler assembly (6616-G), Plug Button (171134), Buttonhead fitting (322108)
7149-T	Multi-Pressure Bucket Pump Assembly w/Porta-Cart	32 lbs. (25kg)	Porta-Cart (6777-5)
7149-V	Multi-Pressure Bucket Pump Assembly w/Porta-Cart	49 lbs. (25kg)	Hose & coupler assembly (6617-G), Porta-Cart (6777-5)



167 Roweland Drive
Johnson City, TN 37601
Toll Free U.S.: 866-4-Alemite
Toll Free Canada: 800-267-8022
International: 803-802-0001
Fax U.S.: 800-648-3917
Fax Canada: 800-267-2880
Fax International: 803-802-0192
www.alemite.com

Recommended Accessories

- Hose Assembly (Hydraulic Narrow Coupler) (322434)
- Hose Assembly (Giant Button Head Coupler) (6615-G)
- Hose Assembly (Standard Button Head Coupler) (322434)
- Hose Assembly (Hydraulic Standard Coupler) (6617-G)

Applications

- Construction • Industrial • Manufacturing • Municipalities • Mining
- Offshore/Oil & Gas Industry